

TASKI

TASKI® swingo 2500



Large ride-on automatic scrubber drier

Key features

- Unbeatable cleaning performance
- Unique ergonomics
- Reliability and durability
- Unrivalled productivity

Unbeatable cleaning performance

A patented all wheel steering system defines new standards in maneuverability; allowing the use of this ride-on machine even in narrow and congested areas. The innovative squeegee concept ensures a 100% edge-to-edge water pick-up even in curves and while turning.

Unique ergonomics

The machine offers a seated operating position coupled with a high working speed. The extremely low noise level, which is comparable to the noise level of a vacuum cleaner, makes work more enjoyable and allows for day cleaning.

Reliability and durability

Fewer mechanical parts and a robust construction makes this machine very reliable. Easily exchangeable brushes and squeegee blades allow simple maintenance and ensures the machine can be easily prepared for use at any time.

Unrivalled productivity

A higher cleaning speed of 7.5 km/h combined with the patented CSD system makes the TASKI swingo 2500 ride on scrubber drier 40% more productive compared to walk-behind scrubber driers.



TASKI[®] swingo 2500

Technical data	
Theoretical performance	5250 m²/h
Working width	70 cm
Squeegee width	93 cm
Solution tank-bag system (nominal)	95 l
Recovery tank-bag system (nominal)	95 l
Rated voltage	24 V
Nominal consumption	2,000 W
Battery capacity (maximum)	240-290 Ah/C5
Battery run time (nominal)	3-5 h
Machine weight ready for use (without driver)	560 kg
Dimensions (L x W x H) (without squeegee)	78 x 169 x 137 cm
Brush pressure (maximum)	52-74 kg
Cleaning speed	7.5 km/h
Transportation speed	9.0 km/h
Sound level	67 dB(A)
Turning circle	1.9 m

The above data is typical of normal production and should not be taken as a specification.

Model	SKU number
TASKI swingo 2500	8004740

Accessories	SKU number
Pad drive harpoon grip drive 35 cm / 43 cm	8501120 / 8501130
Scrubbing brush standard 35/43cm	8501080 / 8505100
Scrubbing brush washed concrete 35 / 43 cm	8501060 / 8501090
Scrubbing brush abrasive 35 / 43 cm	8502917 / 8501919
TASKI JFit kit for swingo 2500	7516241

Additional features

CSD (Cleaning Solution Dosing): The CSD system allows for a speed-dependent supply of cleaning solution. This feature ensures that the amount of solution dosed onto the floor is always constant—no matter how fast the machine is operating. The result? No puddles in curves and turns as well as a 30-50% saving in cleaning solution, leading to significantly increased productivity of the machine.